

# BECKER TECH

## PV-Module



## PM435W(108) TOPCON beidseitig



### SMBB Technology

Better light trapping and current collection to improve module power output and reliability.



### PID Resistance

Excellent Anti-PID performance guarantee via optimized mass-production process and materials control.



### Durability Against Extreme Environmental Conditions

High salt mist and ammonia resistance.



### Hot 2.0 Technology


The N-type module with Hot 2.0 technology has better reliability and lower LID/LETID.




### Enhanced Mechanical Load

Certified to withstand: wind load (2400 Pascal) and snow load (5400 Pascal).

## FRAME



### Linear performance Warranty



### Comprehensive Certificates

IEC61215(2016), IEC61730(2016)

ISO9001:2015: Quality Management System

ISO14001:2015: Environment Management System

ISO45001:2018

Occupational Health and Safety Management Systems



Becker Tech GmbH  
Söderbergstraße 14  
84513 Töging am Inn - Deutschland  
08631-9882033  
service@becker-tech.de



www.becker-tech.de

# PM435W(108) TOPCON beidseitig

Module	PM-435W(108) TOPCON	
Tolerance (W)	0 ~ +3%	
Standard Test	STC	NOCT
Maximum Power (Pmax/W)	435	327
Open Circuit Voltage Voc(V)	37.79V	36.74V
Short Circuit Current Isc(A)	14.45A	11.55A
Maximum Power Voltage Vmp(V)	31.73V	29.75V
Maximum Power Current Imp(A)	13.72A	10.99A
Cells	182 N type TOPCON Mono-crystalline	
Cells Qty (Pcs)	108(2x54)	
Max System Voltage (V)	1000/1500VDC (IEC)	
Temperature coefficients of Pmax	-0.29 %/°C	
Temperature coefficients of Voc	-0.25 %/°C	
Temperature coefficients of Isc	0.045 %/°C	
Operate Temp (°C)	-40 to 85	
Nominal operating cell temperature NOCT	45±2°C	
Max Series Fuse Rating (A)	25A	

## Bifacial Output-Rearside Power Gain / Efficiency

5 % Maximum Power (Pmax)	456 Wp	Module Efficiency STC (%)	23,65 %
15 % Maximum Power (Pmax)	500 Wp	Module Efficiency STC (%)	25,89 %
25 % Maximum Power (Pmax)	543 Wp	Module Efficiency STC (%)	28,12 %


## Raw material

Frame	Anodized Aluminium Alloy	Front Glass	2.0 mm, Anti-Reflection Coating
Cell	108 (2x54pcs)	Back Glass	2.0 mm, Heat Strengthened Glass
Diode Qty	3	Connector / Junction box	4 mm <sup>2</sup> , MC4 or EVO2 / ID68
Cable (mm)	300	Fire Rating	Class A, according to UL 790

## Package


Module size (mm)	1722x1134x30mm	Weight (kg)	24 kg
Loading	936 PCS/40'HQ	Package	36PCS/PLT

## Engineering Drawings




## CURVES

Current-Voltage & Power-Voltage Curves (430W)



Temperature Dependence of Isc, Voc, Pmax



Voltage (V)

